## **©OUTLANDER™ X® mr 1000R**

## HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding
- Front and rear FOX† PODIUM† 1.5 QS3 shocks
- 30-in. ITP Cryptid† tires
- 14-in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- Relocated radiator
- 3,000-lb (1,361 kg) WARN<sup>†</sup> winch with roller fairlead
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad
- · Mud-riding footrests

- Long wheelbase
- Multifunction Analog / Digital gauge
- X-package coloration, graphics and seat cover



Gold, Black & Can-Am Red

ENGINE	1000R
Туре	91 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS		
Front Suspension	Arched double A-arm with front sway bar	
Front Shocks	FOX 1.5 PODIUM QS3	
Rear Suspension	Torsional Trailing arm Independent (TTI)	
Rear Shocks	FOX 1.5 PODIUM QS3	
BRAKES		
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper	

TIRES / WHEELS	
Front Tires	ITP Cryptid† 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid† 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES				
LxWxH	246 x 127 x 131 cm			
Wheelbase	149.9 cm			
Ground Clearance	33 cm			
Seat Height	93.3 cm			
Dry Weight	464 kg			
Rack Capacity	Rear: 90 kg			
Storage Capacity	Rear: 21.4 L			
Towing Capacity	750 kg			
Fuel Capacity	20.5 L			

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers, aluminum taper-profile handlebar with wind deflectors and square pad, mud-riding footrests and mudguards		

WARRANTY		
Factory	2 years	



