MY23 OUTLANDER 450/570 T



Type 28 kW (38 hp), Rotax® 427 cc single cylinder, liquid cooled Fuel Delivery System Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) Transmission CVT, P / R / N / H / L, standard engine braking Drive Train Selectable 2WD / 4WD with Visco-Lok† auto-locking front differential Power Steering N/A Speed Category Up to 60 km/h SUSPENSIONS Front Suspension Double A-arm 9 in. (22.9 cm) travel Front Shocks Oil Rear Suspension Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel Oil TIRES / WHEELS Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic twin-piston caliper	ENGINES	450	570
Electronic Fuel Injection (EFI) Transmission CVT, P / R / N / H / L, standard engine braking Drive Train Selectable 2WD / 4WD with Visco-Lok† auto-locking front differential Power Steering N/A Speed Category Up to 60 km/h SUSPENSIONS Front Suspension Double A-arm 9 in. (22.9 cm) travel Front Shocks Oil Rear Suspension Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel Oil TIRES / WHEELS Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Туре	427 cc single cylinder,	
Drive Train Selectable 2WD / 4WD with Visco-Lok† auto-locking front differential Power Steering N/A Speed Category Up to 60 km/h SUSPENSIONS Front Suspension Double A-arm 9 in. (22.9 cm) travel Front Shocks Oil Rear Suspension Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel Rear Shocks Oil TIRES / WHEELS Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Fuel Delivery System		
with Visco-Lok† auto-locking front differential Power Steering N/A Speed Category Up to 60 km/h SUSPENSIONS Front Suspension Double A-arm 9 in. (22.9 cm) travel Front Shocks Oil Rear Suspension Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel Rear Shocks Oil TIRES / WHEELS Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Transmission	CVT, P / R / N / H / L, standard engine braking	
Speed Category Up to 60 km/h SUSPENSIONS Front Suspension Double A-arm 9 in. (22.9 cm) travel Front Shocks Oil Rear Suspension Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel Rear Shocks Oil TIRES / WHEELS Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Drive Train		
SUSPENSIONS Front Suspension Double A-arm 9 in. (22.9 cm) travel Front Shocks Oil Rear Suspension Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel Rear Shocks Oil TIRES / WHEELS Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Power Steering	N/A	
Front Suspension Double A-arm 9 in. (22.9 cm) travel Front Shocks Oil Rear Suspension Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel Rear Shocks Oil TIRES / WHEELS Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Speed Category	Up to 60 km/h	
9 in. (22.9 cm) travel Front Shocks Oil Rear Suspension Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel Rear Shocks Oil TIRES / WHEELS Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	SUSPENSIONS		
Torsional Trailing arm Independent (TTI)	Front Suspension		
Rear Shocks Oil	Front Shocks	Oil	
TIRES / WHEELS Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Rear Suspension		
Front Tires Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Rear Shocks	Oil	
(63.5 x 20.3 x 30.5 cm) Rear Tires Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	TIRES / WHEELS		
(63.5 x 25.4 x 30.5 cm) Wheels 12-in. (30.5 cm) steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Front Tires		
BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Rear Tires	•	
Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with	Wheels	12-in. (30.5 cm) steel	
hydraulic twin-piston calipers Rear Single 214 mm disc brake with	BRAKES		
	Front		
	Rear	•	

DIMENSIONS / CAPACITIES	450	570
Estimated Dry Weight *	700 lb (318 kg)	720 lb (327 kg)
LxWxH	83 x 46 x 49 in. (211 x 116.8 x 124 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	10.5 in. (26.7 cm)	
Seat Height	33.8 in. (85.8 cm)	
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)	
Storage Capacity	2.9 gal (10.9 L)	
Towing Capacity	750 kg trailer with brakes and 335 kg trailer without brakes	
Fuel Capacity	5.4 gal (20.5 L)	
FEATURES		
Gauge	4.5 in. digital display	
Instrumentation	DC Outlet, 15-A connector	
Ingnition	Mechanical key	
Lighting	70 W headlights	
Winch	N/A	
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	
Seat	Standard	
Seat Handlebar	Standard Standard	
Handlebar	Standard	
Handlebar Protection	Standard	ranty



